


AQUALAB 5TE



Measurement Specifications

WATER ACTIVITY

Range:
0.0300 - 1.0000 a_w

Resolution:
0.0001 a_w

Accuracy:
 $\pm 0.0030 a_w$

Repeatability:
 $\pm 0.0010 a_w$

Drift:
 $\pm 0.0020 a_w$

Sensor type:
Chilled-Mirror Dew Point

MOISTURE CONTENT

Range:
0.00 - 100.00 % MC

Resolution:
0.01 % MC

Accuracy:
 ± 0.5 % of moisture content reference

Repeatability:
0.01 %

Sensor type:
Secondary method - uses moisture sorption isotherm and water activity

TEMPERATURE

Range:
15.00 – 50.00 °C

Resolution:
0.01 °C

Accuracy:
 ± 0.1 °C

READING MODES

- One Minute
- Standard
- Continuous
- Low Emitting
- ISO 18787

READ TIME

Minimum:
60 sec

Typical:
~5 min

CASE DIMENSIONS

Height:
14.7 cm (5.8 in)

Width:
32.5 cm (12.8 in)

Depth:
29.2 cm (11.5 in)

AQUALAB 5TE

Functional Specifications

Modular swappable block:

The sensor block is easily swappable for service or repair.

Touchscreen:

Features a touchscreen with sufficient size and resolution to adequately convey a simplified and streamlined interface for water activity measurements. (7 inch display with 1024 × 600 pixel resolution)

PCAP touch interface

- Capable of detecting keypresses and swipe gestures
- Supports latex, nitrile (single or double layer), butyl, and neoprene gloves
- Easily cleanable.

Ease-of-use:

- Usable even by untrained users.
- On-screen help for operation and troubleshooting.
- Multilingual native support for English, Spanish, French, Chinese, Japanese, Portuguese, German, Polish, and Italian.

Sealable sample chamber:

- Used to equilibrate samples during measurement in order to determine water activity.

Speaker:

- For status alerts, user-configurable on/off.

USB 2.0 support:

- 4 x USB-A ports to support keyboards, mice, wireless network adapters, USB drives, and barcode scanners
- 1 x USB-B receptacle for CSV and PDF export of data directly to a PC

LED light bar:

- Instant reading and instrument status from across the room.

Network connection:

Ethernet via USB-A to Ethernet adapter

- At least 100 mbps support
- Wiring TIA/EIA-568B

Wireless network

Via an adapter dongle

- 2.4 GHz band
- 802.11 b/g/n protocols
- At least 100 Mbps support

Supports dynamic and static IPs, router, subnet mask and DNS server configurations.

Network requirements:

For cloud connectivity, the instrument must be able to connect to cloud.aqualab.com